

## 3. Specifications

Specifications are correct at the time of printing. Product specifications are subject to change without notice. See below for product specifications.

Items			SF-565P Series	
Model Name			SF-565P	SF-560
Functions			Fax,Copier,Printer,Scanner	Fax,Copier
General	Size (W*D*H) w/o Hand Set		363.0 * 398.0 * 308.3(mm)	363.0 * 398.0 * 308.3(mm)
	Weight Without Toner Cartridge		10kg	10kg
	With Toner Cartridge		11.5kg	11.5kg
	LCD		16*2	16*2
	Interface		IEEE1284, USB 1.1	USB 1.1 : f/w Down Load
	AMV(Average Month Volume)	Printing	500	-
		Scan to Copy or Scan to Fax	500	500
	Duty cycle, Monthly	Printing	Up to 10,000 pages	Up to 10,000 pages
		ADF SCAN	Up to 2,000 pages	Up to 2,000 pages
Engine Life			Up to 120,000 Pages	Up to 120,000 Pages
Power Consumption	Power Switch		Yes	Yes
	Input Voltage		AC110V~127V, 220V ~ 240V	AC110V~127V, 220V ~ 240V
	Power Sleep Mode		Energy Star Compliant	Energy Star Compliant
**Noise	Operating(ADF)		Less than 52 dBA	Less than 52 dBA
	Standby		Less than 39 dBA	Less than 39 dBA
	Printing		Less than 509 dBA	Less than 50 dBA (Fax Rec., Memory Copy)
EMI Approval	EMI Approval		Class B	Class B
PC Print	Power Save Mode		Yes (5/10/15/30/45min.off)	Yes (5/10/15/30/45min.off)
	Print Method		Laser	Laser
	N/W I/f		No	No
	* Speed (Engine)		Up to 16 PPM in A4 size, Up to 17 PPM in Letter size	-
	Resolution	Normal	Up to 600 x 600 DPI effective output	-
		RET	No	-
	Print Language		GDI	-
	Toner Save		Yes	Yes(Text Mode)
	Fpot	Stand by	Approx. 12 seconds	-
		Power Save	Less than 42 seconds	-
	Printable Area		208 x 273 mm (Letter)	-
	Duplex Print		Manual (driver support provided)	-

\* Speed will be affected by Operating System used, computing performance, application software, connecting method, media type, media size and job complexity.

\*\* Sound Pressure Level, ISO 7779

Items			SF-565P Series	
Model Name			SF-565P	SF-560
Scan	Halftone		256level	256level
	Scan Method		"CIS, Mono"	"CIS, Mono"
	*Scan Speed (Second /scan)	Gray	Up to 72 sec	-
		Color	-	-
		Black&White	Up to 25 sec	-
	Resolution(Optical)		Up to 200 x 200 DPI effective output	Up to 200 x 200 DPI effective output
	Halftone		256level	-
	Scan Width	Max	216mm	-
		Effective	208mm	-
	Scan Length	Max	400mm	-
Copy	Speed		Up to 16 PPM in A4 size, Up to 17 PPM in Letter size	Up to 16 PPM in A4 size, Up to 17 PPM in Letter size
	Resolution		Up to 300 x 300 DPI effective output	Up to 300 x 300 DPI effective output
	Halftone		256level	256level
	Copy Quality Selection or Original Image type selection Mode	Text	16sec/Letter	16sec/Letter
		Photo	16sec/letter	16sec/letter
	FCOT	Power Save	Yes	Yes
		Stand by	approx : 30sec	approx : 30sec
	*Copy Speed	SDMC	Up to 16 PPM in A4 size, Up to 17 PPM in Letter size	Up to 16 PPM in A4 size, Up to 17 PPM in Letter size
		MDMC	3cpm	3cpm
Telephone	Zoom Range		50-150%	50-150%
	Multi Copy		1~99	1~99
	Handset		Yes (Germany: No)	Yes (Germany: No)
	1-Touch Dial		20	20
	Speed Dial		80	80
	TAD		No	No
	TAD I/F		Yes	Yes
	Tone/Pulse		Tone (DTMF)	Tone (DTMF)
			Pulse : setting in tech mode	Pulse : setting in tech mode
Fax	Earth/Recall		No	No
	SMS		No	No
	External Phone Interface		Yes	Yes
	Compatibility		ITU-T G3	ITU-T G3
	Communication System		PSTN/PABX	PSTN/PABX
	Modem Speed		33.6Kbps	33.6Kbps
	TX Speed		approx. 3 sec	approx. 3 sec
	Compression		MH/MR/MMR	MH/MR/MMR
	ECM		Yes	Yes
	Resolution	Std	Up to 203 x 98 DPI effective output	Up to 203 x 98 DPI effective output
		Fine	Up to 203 x 196 DPI effective output	Up to 203 x 196 DPI effective output
		S.Fine	Up to 203 x 392 DPI effective output	Up to 203 x 392 DPI effective output
		Std	Up to 6 sec	Up to 6 sec
		Fine	Up to 12 sec	Up to 12 sec
		S.Fine	Up to 24 sec	Up to 24 sec

Items			SF-565P Series	
Model Name			SF-565P	SF-560
Fax (Continued)	Halftone		256level	256level
	Memory	Capacity	Total memory: 8MB( Fax: 2MB)	Total memory: 8MB(Fax: 2MB)
		Optional Memory	No	No
		Broadcasting	Yes	Yes
		Delay TX	Yes	Yes
		Memory RX	Yes	Yes
	Functions	Voice Request	No	No
		TTI	Yes	Yes
		RTI	Yes	Yes
		Polling	Rx Polling	Rx Polling
		Security Receive	Yes	Yes
		Flash	No	No
		Auto Reduction	Yes	Yes
		"F/W Upgrade from Remote"	Yes	Yes
	Memory B/U		Yes(96 Hour)	Yes(96 Hour)
Paper Handling	Cassette	Type	Cassette	Cassette
		Input Capacity	250Sheets/20lb	250Sheets/20lb
		Optional Cassette	No	No
		Output Capacity	Max. 150 sheets/20lb	Max 150 sheets/20lb
		Output Control	Face down	Face down
		Bypass	1sh	1sh
		Media Size for Main Tray	For Fax and Copy: A4,Letter, Legal For PC Print : A4,Letter, Legal. Folio, Executive, B5	For Fax and Copy: A4,Letter, Legal For PC Print : A4,Letter, Legal. Folio, Executive, B5"
		Media Size for Bypass	Envelope6 3/4, 7 3/4,#9, #10,DL,C5,B5	Envelope6 3/4, 7 3/4,#9, #10,DL,C5,B5
		Media Weight	Auto : 16 ~ 28 lb Bypass: 16 ~ 43 lb	Auto : 16 ~ 28 lb Bypass: 16 ~ 43 lb
	ADF	Input Capacity	Min. 20 Sheets	Min. 20 Sheets
		Media Weight	12.5lb ~ 28lb, 32lb(1 sheet)	12.5lb ~ 28lb, 32lb(1 sheet)

\* Copy or Scan speed will be affected by Operating System used, computing performance, application software, connecting method, media type, media size and job complexity.

Items			SF-565P Series	
Model Name			SF-565P	SF-560
Software	Windows Compatiblity (Scan/Print)	DOS	No	No
		Win 3.x	No	No
		Win 95	Yes	No
		Win 98&WinME	Yes	No
		Win NT 4.0	Yes	No
		Win 2000	Yes	No
		Win XP	Yes	No
	Driver	GDI Printer	SPL	No
		TWAIN	Yes	No
		FaxRCP (Windows ONLY)	Yes	No
		Mac Printer	Yes	No
		Mac Scanner	No	No
		Linux Printer	Yes	No
		Linux Scanner	Yes	No
		PC-FAX	No	No
	M/S Certification	WHQL	Yes (WinXP Printer driver only)	-
		WIA	No	No
	Bundle S/W		SmarThru 3	-
	Media	CD-ROM	Yes	-
		Manual	Standalone Fax: Book MFP: CD	Standalone Fax: Book
		Diskette	No	No
Consumables	Life	Initial	1,000 Pages	1,000 Pages
		Running	3,000 Pages	3,000 Pages
	Toner Sensor (Software)		Yes(Dot Counter)	Yes(Dot Counter)
Periodic Replacing Parts			Pick Up Roller : Up to 60,000 sheets Transfer Roller : Up to 60,000 sheets Fuser Assembly : Up to 60,000 sheets ADF Roller : Up to 60,000 sheets ADF Rubber : Up to 10,000 sheets	