


ACCESSIBILITY HANDLE-A1 INSTALLATION PROCEDURE

Follow the instructions herein when installing the Handle to a DADF.

1 Checking the Contents



- [1] Support plate 1 pc.
- [2] Binding screw (M4x6) 3 pc.
- [3] Handle 1 pc.
- [4] Stepped screw (M4x30) 1 pc.
- [5] Hinge angle guide plate* 1 pc.

**Used only if installation is to a DADF-H1.*

Figure 1-1

2 Installation Work

The instructions that follow refer to installation to a DADF-D1. Be sure to keep the following points in mind for the work:

1. The host machine and the DADF must have been properly installed before starting the work.
 2. The power plug of the host machine must remain disconnected.
- 1) Open the DADF.
 - 2) Remove the face sticker [1] and the face plate [2] from the right side of the DADF. (if for a DAFD-D1)



You will no longer be using the removed face sticker or face plate.




Figure 2-1

- 3) Fit the support plate [1] from the inside right of the original delivery assembly cover of the DADF, and secure it in place to the DADF using 2 screws [2] (binding; M4x6).




Figure 2-2

- 4) Secure the handle [1] using a stepped screw [2] so that the guide plate [3] shown in Figure 2-2 is inside the handle.




Figure 2-3

- 5) Secure the hinge guide plate [1] to the left hinge of the DADF using a screw [2]. (if for a DADF-H1)




Figure 2-4

- 6) Working from the front of the host machine and using the handle [1], close the DADF as if to pull it down, thereby making sure that the handle has properly been installed.




Figure 2-5