

Model:

LaserBase MF6530
LaserBase MF6540PL
LaserBase MF6550
LaserBase MF6560PL
LaserBase MF6580PL

Ref No.:

MF6500-020
(F9-T01-M00-10041-01)

Date:

November 2007

Location:


Internal Components 2


Subject:

Improving the reliability of contact area between the contact spring unit and the cartridge

Detail:

Additionally, the new shape of contact spring unit and adjacent parts are newly set up as the cartridge guide assembly [B].





P-2

P-2 Contact spring unit

[1] Old type

[2] New type

Points to note about service work:

When replacing the contact spring unit of a machine having a serial number earlier than the ones listed in the “Affected machines” section below, use the old type contact spring unit [1], or perform the replacement with the cartridge guide assembly (FM3-2400).

For a machine having one of the serial numbers listed in the “Affected machines” sections below, use the new type of contact spring unit [2], or perform the replacement with the cartridge guide assembly (FM3-2400).

Service parts:

No.		Part number	Part name	Q'ty	Stock	Compati- bility	Available from	Fig. No.
1	O	FC6-7324-000	SPRING UNIT, CONTACT	1 > 1	B	N	End of Oct.	102
	N	FC7-9933-000	SPRING UNIT, CONTACT	0 > 1	D	N		
2	O						End of Oct.	102
	N	FM3-2400-000	CARTRIDGE GUIDE ASSEMBLY	0 > 1	D			

Affected machines:

i-SENSYS MF6530 (EU1)	BAC02946 and later
i-SENSYS MF6550 (EU1)	DAC03161 and later
i-SENSYS MF6540PL (EU1)	EAC04003 and later
i-SENSYS MF6560PL (EU1)	FAC03073 and later
i-SENSYS MF6580PL (EU1)	GAC02833 and later
i-SENSYS MF6530 (EU2)	HAC02121 and later
i-SENSYS MF6550 (EU2)	NAC03737 and later
i-SENSYS MF6540PL (EU2)	PAC02633 and later
i-SENSYS MF6560PL (EU2)	QAC03593 and later
i-SENSYS MF6580PL (EU2)	SAC02105 and later
i-SENSYS MF6550 (EU3)	VAC03185 and later
i-SENSYS MF6560PL (EU3)	WAC02665 and later
i-SENSYS MF6580PL (EU3)	XAC03025 and later