

KM-1530

discover

► high performance in a remarkably compact design



- 15 pages per minute in A4, 8 pages per minute in A3 (18 copies A4 per minute with additional memory)
- Fastest in its segment: first copy in less than 5.5 seconds
- High resolution: 600 x 600 dpi (2400 x 600 dpi with KIR2)
- 300-sheet capacity as standard, upgradeable to 1,050 sheets
- 70-sheet document processor (optional)
- Long-life components, easy maintenance
- Low total cost of ownership

► print ► copy ► scan ► fax

The space saving KM-1530 is modular in design and can be utilised as a stand-alone digital copier or connected as a fully-featured network printer. Upgradeable into a versatile workgroup printer, the optional network interface card provides seamless integration with the majority of computer networks. With a warm-up time of 30 seconds and a first copy time of less than 5.5 seconds, the KM-1530 is the fastest in its segment. The compact design with its internal output tray puts the KM-1530 amongst the smallest copiers in its class, even with all accessories. The incredibly small, low-noise KM-1530 is an asset to the small and medium sized office environments.

KM-1530

Monochrome A3 multifunctional

The KM-1530 incorporates extremely durable components that guarantee smooth and reliable operation. The system is designed to last for extreme long hardware maintenance cycles after 100,000 pages. Thus, the KM-1530 keeps your overall operating costs low and high productivity – at the same time ensuring a minimum impact on the environment.

GENERAL

Technology: Kyocera Laser

Type: Desktop

Engine speed: Max. 15/8 pages A4/A3 per minute

Max. 18/9 pages per minute A4/A3 with MB-5A

Resolution: 600 x 600 dpi, 256 greyscales (copy),

600 x 600 dpi, 2400 x 600 dpi with KIR2 (print)

Time to first copy: 5.5 seconds or less

Warm-up time: 30 seconds or less

Duty cycle: Max. 20,000 pages per month

Power Source: AC 220 V ~ 240 V, 50/60 Hz

Power Consumption: Copying: 639 W, Stand-by: 42 W

Noise (ISO 7779): Copying: 65 dB(A), Stand-by: 37 dB(A)

Dimensions (W x D x H): 550 x 560 x 498 mm

Weight: Approx. 38 kg

Certification: GS/TÜV/CE

This product is produced according to the quality norm ISO 9001 and the environmental guidelines ISO 14001

PAPER HANDLING

All mentioned paper capacities are based on 80g/m² paper with a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera Mita under normal environmental conditions.

Input capacity: 250-sheet universal feeder, 64-80g/m², A3, A4, A5, Folio

50-sheet multi-purpose tray, 45-160g/m², A3, A4, A5, A6, Folio, Envelopes,

Max. 1,050 sheets

Output capacity: 250-sheet face-down

System Platform

The KM-1530 delivers outstanding network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE IIe

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (and multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

Typefaces and barcodes

The 80 scalable PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

COPY FUNCTIONS

Max. original size: A3

Continuous copy: 1 - 250

Memory capacity: Optional 32 MB RAM

Zoom range: 50 - 200% in 1% steps

Present magnification ratios: 13R / 9E

Digital copy features: Energy save mode, interrupt copy, scan-once-print-many^{*1}, electronic sort copy^{*1}, rotate sort copy^{*2}, layout mode (2-in-1, 4-in-1), margin shift, border erase, management mode (max. 100)

^{*1} Requires optional MB-5A

^{*2} Requires optional MB-5A and additional ST-12

Exposure mode: Auto, Manual: 5 or 9 steps

Image adjustments: Text + Photo, Text, Photo

PRINT FUNCTIONS (optional)

Processor: PowerPC 450GF/200Mz

Memory: Standard 8 MB, Max. 136 MB, 1 additional DIMM slot (16, 32, 64, 128 MB)

Emulations: PCL5e, PCL6 incl. PJJ, KPDL2

(PostScript2 compatible), Line printer, IBM Proprinter, Epson LQ850, Diablo 630

Controller language: PRESCRIBE IIe

Fonts: 80 outline fonts (PCL/KPDL), 1 Bitmap font

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), KUJO-LV slot for optional interface

Multiple interface connection (MIC): Allows for simultaneous data transfer via up to two interfaces, with each interface having its own virtual printer.

KM-NET VIEWER

KM-NET VIEWER is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET VIEWER also acts as a valuable, real-time early warning system by sending e-mail messages.

CompactFlash® card

The CompactFlash® card offers abundant storage space for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

OPTIONS

Printing System (K)

Paper handling

STDF-3 Document processor: 70-sheet, Simplex scan,

35-160g/m², A5R-A3, Folio,

ST-12 Paper feeder: 250-sheet, 64-80g/m², A5R-A3, Folio,

(Max. 3 ST-12)

J-1302 Job separator: 100-sheet, 64-80g/m², A5R-A3, Folio

Memory

Copy memory

MB-5A: 32 MB

Printer memory

DIMM memory: 1 slot (16, 32, 64, 128 MB DIMM)

CompactFlash card: 1 slot (8, 16, 32, 64 MB DIMM) forms, fonts, logo, macro storage

Optional interface

IB-21E Network card: 10Base-T/100Base-TX

SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic

SB-140 Network card: 10Base-2/10Base-T/100Base-TX

SB-50 Network card: 10Base-FL, FibreLink

SB-60 Network card: TokenRing STP/UTP

SB-70 Network card: Wireless LAN - IEEE 802.11b

SB-80 Parallel interface: 2nd Parallel interface (IEEE 1284)

IB-11 Serial interface: RS-232C Serial interface

(up to 115.2 kbps)

Others

Platen cover (B): Platen cover

AOSD: Automatic original size detection

Cabinet: High/Low & wooden / metal desk with storage capacity

CONSUMABLES

Toner Kit: Microfine toner for 11,000 pages with 6% A4 coverage



Your Kyocera Mita Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands,
Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

KM-1530-English-8DSE1530. Kyocera Mita does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

